

MSA-1512-W2E

- premium quality plug type 12 V power supply

FEATURES:

- compact design
- high power output
- premium class design
- safe and reliable power source
- high power efficiency, low standby

APPLICATIONS:

- consumer electronics
- office equipment
- general purpose
- computer devices
- home and building automation
- security and monitoring systems
- POS, POI equipment

MSA-1512-W2E is a compact and efficient 15-watt wall-mounted style plug type power unit for various types of electronic devices. It is based on high quality electronic components that allow continuous, long-lasting work in all conditions. It is reliable, fully secured and stable. It provides high efficiency and excellent specification.




TECHNICAL SPECIFICATION

Group	Parameter	Value	Conditions
Input	Rated input voltage	100-240 VAC	
	Input voltage range	90-264 VAC	
	Mains frequency range	47-63 Hz	
	AC current (max.)	0.6 A	At 100 VAC and full load
	Inrush current (max.)	30 A	
	No load power consumption	75 mW	
	Input leakage current (max.)	0.25 mA	At 264 VAC
Output	Rated output voltage	12 V	
	Rated output power	14 W	
	Rated output current	1.2 A	
	Average efficiency	84,28%	At 230 VAC
	Power efficiency at 10% load	84%	
	Line regulation	±1%	
	Load regulation	±5%	
	Ripple and noise	100 mVp-p	At 100 VAC
	Minimal output current	No	
	Hold up time (max.)	20 ms	At 230 VAC and full load
	DC voltage rise time (max.)	10 ms	At 230 VAC and full load
	Turn on delay time (max.)	3 s	At 100 VAC
Environmental	Working temperature	0 to +40°C	
	Working humidity	10% to 90% RH	40°C
	Storage temperature	-20°C to +80°C	
	Cooling method	Free air circulation	
Protection	Short circuit	Yes	
	Overcurrent	Yes	
	Output overvoltage	Yes	
	Automatic recovery on fault remove	Yes	
Safety and EMC	Withstand isolation voltage	3 kVAC (input to output)	10 mA, 1 min
	Isolation resistance	100 MΩ	500 VDC
	Isolation class	2	
	Safety compliance	EN60950-1	
	EMC compliance	EN55032 EN55024 EN 61000-3-x EN 61000-4-x	
	Marking	RoHS, CE	
Mechanical and features	Enclosure	Black ABS plastic	
	Size	73 × 33 × 69 mm	L × W × H
	Weight	124 g	
	Output connector	DC Jack 2.1 × 5.5 × 11 mm	Plus in the middle
	Input connector	EU 2-pole plug	
	Output cable	1.5 m	0.32 mm ²
	Single package	PE bag	
	Packing	450 × 390 × 335 mm	60 items
	Manufacturing	China	
	Warranty	3 years	


Notes:

Unless otherwise stated, all parameters are specified at 230 VAC input voltage, 50 Hz, ambient temperature 25°C and relative humidity 70% for rated load output. The values of parameters related to the output voltage regulation is measured from low to high line or for load changes from 0 to 100%, respectively. The power supply is considered as an independent unit, but the final equipment still need to reconfirm that the whole system complies with the EMC directives. If the PSU is installed in the final device as a subassembly, the tests should be repeated to verify that the system has been met compliance. Detailed technical data are available on request.


BLOCK DIAGRAM



MECHANICAL SPECIFICATION



PRODUCT LABEL



- Legend to the label icons:
- - II safety class: no grounding is required, no dangerous voltage even in an emergency situation will appear on output
 - 🏠 - power supply intended for indoor use only
 - VI - high efficiency and low no load power consumption, meeting the requirements of Energy Star Compliance Level 6
 - ⊕ - polarization: plus in the middle, minus outside
 - ♻️ - the product must not be disposed of in normal waste containers

MARKING SYSTEM
MSA-1512-W2E

- Mains plug **W2E**
- Rated output voltage **12 V**
- Output power **15 W**
- Family **MSA**

OTHER POWER SUPPLIES IN THIS SERIES

Model	ESPE-O112-W2E	ESPE-O312-W2E	ESPE-O612-W2E	ESPE-1212-W2E	MSA-1512-W2E	ESPE-1812-W2E	ESPE-2412-W2E
Rated output voltage	12 V	12 V	12 V	12 V	12 V	12 V	12 V
Rated output current	0.1 A	0.3 A	0.5 A	1 A	1.2 A	1.5 A	2 A
Rated output power	1.2 W	3.6 W	6 W	12 W	14 W	18 W	24 W