

256K nMOS Dynamic RAM (65536x4) 18PIN 41464

型名	社名	温度範囲 (°C)	スイッチング特性								電 源			入力 [*typ]			出力 [*typ]			リフレ ッシュ Cyc/ms	備 考
			TRAC max (ns)	TRCY min (ns)	TCAD min (ns)	T <sub>1</sub> AH min (ns)	T <sub>1</sub> P min (ns)	TWCY min (ns)	TDH min (ns)	TRWC min (ns)	VDD or VCC (V)	I <sub>DD</sub> max (mA)	I <sub>DD</sub> STANDBY (1SB/1SB2) (mA)	V <sub>IL</sub> max (V)	V <sub>IH</sub> min (V)	C <sub>i</sub> max (pF)	V <sub>OL</sub> /I <sub>VOL</sub> max (V/mA)	V <sub>OH</sub> /I <sub>VOH</sub> min (V/mA)	C <sub>o</sub> max (pF)		
MB81464-10	FUJITSU	0~70	100	200	20	15	80	200	25	270	4.5~5.5	70	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	
MB81464-12	FUJITSU	0~70	120	220	22	20	90	220	30	305	4.5~5.5	65	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	
MB81464-12-W	FUJITSU	-55~110	120	250	22	20	120			325			6/-	0.8	2.4	10	0.4/4.2	2.4/5	7		PAGE MODE
MB81464-15	FUJITSU	0~70	150	260	25	25	100	260	35	345	4.5~5.5	57	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	
MB81464-15-W	FUJITSU		150	280	25	25	120			365			6/-	0.8	2.4	10	0.4/4.2	2.4/5	7		PAGE MODE
MC41464A-10	MOTOROLA	0~70	100	190	20	20	80	190	30	260	4.5~5.5	80	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	
MC41464A-12	MOTOROLA	0~70	120	220	25	25	90	220	35	300	4.5~5.5	72	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	PAGE MODE
MC41464A-15	MOTOROLA	0~70	150	260	25	35	100	260	45	355	4.5~5.5	63	5/-	0.8	2.4	7	0.4/4.2	2.4/5	7	256/4	PAGE MODE
MN41464-12	MATSUSHITA	0~70	120	220	25	20	90	220	25	300	4.5~5.5	70	5/-	0.8	2.4	8	0.4/4.2	2.4/5	8	256/4	
MN41464-15	MATSUSHITA	0~70	150	260	25	25	100	260	30	355	4.5~5.5	60	5/-	0.8	2.4	8	0.4/4.2	2.4/5	8	256/4	
MN41464A-10	MATSUSHITA	0~70	100	190	20	100	80	190	20	265	4.5~5.5	70	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464A-12	MATSUSHITA	0~70	120	220	25	120	90	220	25	300	4.5~5.5	65	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464A-8	MATSUSHITA	0~70	80	160	20	80	70	160	15	230	4.5~5.5	80	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464AJ-10	MATSUSHITA	0~70	100	190	20	100	80	190	20	265	4.5~5.5	70	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464AJ-12	MATSUSHITA	0~70	120	220	25	120	90	220	25	300	4.5~5.5	65	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464AJ-8	MATSUSHITA	0~70	80	160	20	80	70	160	15	230	4.5~5.5	80	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464AL-10	MATSUSHITA	0~70	100	190	20	100	80	190	20	265	4.5~5.5	70	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464AL-12	MATSUSHITA	0~70	120	220	25	120	90	220	25	300	4.5~5.5	65	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464AL-8	MATSUSHITA	0~70	80	160	20	80	70	160	15	230	4.5~5.5	80	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464AS-10	MATSUSHITA	0~70	100	190	20	100	80	190	20	265	4.5~5.5	70	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464AS-12	MATSUSHITA	0~70	120	220	25	120	90	220	25	300	4.5~5.5	65	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464AS-8	MATSUSHITA	0~70	80	160	20	80	70	160	15	230	4.5~5.5	80	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464AZ-10	MATSUSHITA	0~70	100	190	20	100	80	190	20	265	4.5~5.5	70	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464AZ-12	MATSUSHITA	0~70	120	220	25	120	90	220	25	300	4.5~5.5	65	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MN41464AZ-8	MATSUSHITA	0~70	80	160	20	80	70	160	15	230	4.5~5.5	80	3/-	0.8	2.4	6	0.4/4.2	2.4/5	6	256/4	
MS51464-12	MOSEL	0~70	120	220	22	20	90	220	30	305	4.5~5.5	65	5.0/-	0.8	2.4	10	0.4/4.2	2.4/5	7	256/4	P
MS51464-15	MOSEL	0~70	150	260	25	25	100	260	35	345	4.5~5.5	57	5.0/-	0.8	2.4	10	0.4/4.2	2.4/5	7	256/4	P
MSM41464-12AS	OKI	0~70	330	230	25	15	100	230	25	330	4.5~5.5	60	5/-	0.8	2.4	6	0.4/4.2	2.4/5	10	255/4	
MSM41464-12RS/JS	OKI	0~70	330	230	25	15	100	230	25	330	4.5~5.5	60	5/-	0.8	2.4	6	0.4/4.2	2.4/5	10	255/4	
MSM41464-15AS	OKI	0~70	375	260	30	20	100	260	30	375	4.5~5.5	60	5/-	0.8	2.4	6	0.4/4.2	2.4/5	10	256/4	
MSM41464-15RS/JS	OKI	0~70	375	260	30	20	100	260	30	375	4.5~5.5	60	5/-	0.8	2.4	6	0.4/4.2	2.4/5	10	256/4	
MT1259-10	MICRON	0~70	100	190	25	100	80	190	35	220	4.5~5.5	55	5/-	0.8	2.4	8	0.4/5	2.4/5	7	256/4	
MT1259-12	MICRON	0~70	120	220	25	120	90	220	40	255	4.5~5.5	55	5/-	0.8	2.4	8	0.4/5	2.4/5	7	256/4	
MT1259-15	MICRON	0~70	150	260	25	150	100	260	45	295	4.5~5.5	45	5/-	0.8	2.4	8	0.4/5	2.4/5	7	256/4	
MT1259-8	MICRON	0~70	80	150	20	80	60	150	15	180	4.5~5.5	65	5/-	0.8	2.4	8	0.4/5	2.4/5	7	256/4	
MT4064-12	MICRON	0~70	120	220	25	20	90	220	40	265	4.5~5.5	75	6/-	0.8	2.4	7	0.4/5	2.4/2	8	256/4	
MT4064-15	MICRON	0~70	150	260	30	25	100	260	45	310	4.5~5.5	75	6/-	0.8	2.4	7	0.4/5	2.4/2	8	256/4	
MT4064-20	MICRON	0~70	200	330	40	30	120	330	55	390	4.5~5.5	75	6/-	0.8	2.4	7	0.4/5	2.4/2	8	256/4	
MT4067-10	MICRON	0~70	100	190	25	100	80	190	35	250	4.5~5.5	55	5/-	0.8	2.4	8	0.4/5	2.4/5	7	256/4	
MT4067-12	MICRON	0~70	120	220	25	120	90	220	40	295	4.5~5.5	55	5/-	0.8	2.4	8	0.4/5	2.4/5	7	256/4	
MT4067-20	MICRON	0~70	15	260	25	150	100	260	45	345	4.5~5.5	45	5/-	0.8	2.4	8	0.4/5	2.4/5	7	256/4	
MT4067-80	MICRON	0~70	80	150	20	80	60	150	15	200	4.5~5.5	65	5/-	0.8	2.4	8	0.4/5	2.4/5	7	256/4	