

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

## Technical Datasheet



### **FirestoP® tasker® TSK 1038 – 2x0,35 mm<sup>2</sup>**

### **DMX Digital Audio 110 Ohm Cable AES/EBU**



A

B

C

D

E

**CATEGORY** Digital Audio Cable (See Audio Catalogue)

**APPLICATIONS** Digital Audio Applications and DMX Light

- A:** Soft **Flame Retardant PVC** – Available in different colors.  
Outer cable Diam. Ø 6,30 (±0,20) mm.
- B:** Shielding O.F.C. tinned copper Braid covering 85% + O.F.C. tinned copper Drain Wire.
- C:** Waste filler between conductors and total taping in not woven polyester.
- D:** Core Insulation with PPE, colored one Red and one Blue.  
Core Diam. Ø 1,60 (±0,20) mm.
- E:** O.F.C. tinned copper formation 11x0,20 mm.  
Nom. Cross section 2x0,35 mm<sup>2</sup>.

**MARKING** **tasker®** TSK 1038 2x0,35 - 22 AWG O.F.C. Extra Flex Digital 110 Ω DMX Audio Cable FirestoP® Italy

**CUSTOM PRODUCTION** This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,** or Metallic Armored.

#### Cable Properties

<b>Conductor Resistance</b>	58,00 Ω/Km
<b>Capacity Core/Core</b>	55 pF/mt
<b>Capacity Core/Shield</b>	62 pF/mt
<b>Impedance</b>	110 Ω
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-20/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			