



ELECTRICAL DATA:			
TESTS	CONDITIONS	ACCEPTANCE CRITERIA	
Iex	@ 3V, 500Hz, PIN 1 - PIN 3	2mA	Max.
Sec. N.L.V	@ 3V, 500Hz, PIN 1 - PIN 3		
	PIN 2 - PIN 3 =	1.500V	\pm 2%
	PIN 6 - PIN 7 = PIN 7 - PIN 8 =	1.062V	\pm 2%
	PIN 6 - PIN 8 =	2.124V	\pm 2%
DCR	@ 20°C, PIN 1 - PIN 3 =	79.70 Ω	\pm 20%
	@ 20°C, PIN 6 - PIN 8 =	53.30 Ω	\pm 20%
HIPOT	PRIMARY - SECONDARY	100V, 60Hz, 1 SEC	

REV.#	REVISION	DATE	HAMMOND ELECTRONIC DIVISION		52 RANKIN PLACE, WATERLOO, ONTARIO, N2J 3Z5		PH # (519) 886-6181
0	RELEASED.	C.I. 05/21/19	MANUFACTURING™				FAX # (519) 886-9540
			DWG. BY: C. ILIE	CHK'D BY:	TITLE: AUDIO TRANSFORMER	DWG. NO. 101H	
			DATE: 05/21/19	APP'D. BY:			
				DIMENSIONS: IN(X) MM()			