



ELECTRICAL DATA:		
TESTS	CONDITIONS	ACCEPTANCE CRITERIA
Iex	@ 3V, 500Hz, PIN 1 - PIN 3	5.8mA Max.
Sec. N.L.V	@ 3.0V, 500Hz, PIN 1 - PIN 3	
	PIN 2 - PIN 3 =	1.500V ±2%
	PIN 6 - PIN 7 = PIN 7 - PIN 8 =	0.609V ±2%
	PIN 6 - PIN 8 =	1.218V ±2%
DCR	@ 20°C, PIN 1 - PIN 3 =	20.40 Ω ±20%
	@ 20°C, PIN 6 - PIN 8 =	4.800 Ω ±20%
HIPOT	PRIMARY - SECONDARY	100V, 60Hz, 1 SEC

REV.#	REVISION	DATE	HAMMOND ELECTRONIC DIVISION	
0	RELEASED. C.I.	01/22/16	52 RANKIN PLACE, WATERLOO, ONTARIO, N2J 3Z5	
			PH # (519) 886-6181	
			FAX # (519) 886-9540	
			DWG. BY: C. ILIE	CHK'D BY:
			DATE: 01/22/16	APP'D. BY:
			DIMENSIONS: IN(X) MM()	TITLE: AUDIO TRANSFORMER
				DWG. NO. 101P